



ABATRON, INC.

5501 - 95th Ave., Kenosha, WI 53144 U.S.A
(262) 653-2000 www.abatron.com
24 Hour Emergency No: 800/424-9300

Material Safety Data Sheet

Code: WoodEpoX A

Page: 2

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: WoodEpoX A
Product Code: WoodEpoX A
Class: Filled epoxy compound

Date Prepared: 06/28/2006
Type: Adhesive Paste

Oral: Low in toxicity.

Systemic: Human effects not established. No specific antidote. Treatment should be based on the sound judgment of the physician and the individual reaction of the patient.

SECTION 2: HAZARDOUS INGREDIENTS

Trade Secret: Proprietary Diglycidyl Ether Resin Mixture

SECTION 3: PHYSICAL DATA

Boiling Point: NA
Vapor Press: NA
Vapor Density (Air=1): NA

Sol. In Water: None
Sp. Gravity: <1
% Volatile by Vol.: <0.1

Appearance And Odor: White (also other colors) thixotropic paste. Almost no odor.

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

Flash Point: >450 °F

Flammable Limits (STP in Air)

Method Used: ASTM D 92-96 TOC

LFL: Not deter **UFL:** Not deter

Extinguishing Media: Foam, CO₂, dry chemical

Special Fire Fighting Equipment and Hazards: None

SECTION 5: HEALTH HAZARD DATA

Occupational Exposure Limits:

OSHA PEL/TWA: Not established

PEL/STEL: Not established

ACGIH TLV/TWA: Not established

Ingestion: Low Single Oral Toxicity LD50 (Rat) : >2000 mg/kg.

Eye Contact: Minor transient irritation. No corneal injury likely.

Skin Contact: Only minor irritation. May be a skin sensitizer.

Skin Absorption: Not likely to be absorbed in toxic amounts.

Inhalation: Not likely a problem at room temperature. Vapors from heated material may be irritating.

Effect Of Overexposure: None known.

First Aid Procedures:

Eyes: Irrigate with flowing water immediately for 5 minutes. Refer to medical personnel.

Skin: Contact will probably cause no more than irritation. Flush skin with water or soap and water. Wash clothing before reuse.

Inhalation: Remove to fresh air if effects occur. Consult medical personnel

Ingestion: Low in toxicity. Induce vomiting if large amounts are ingested.

Note to Physician

Eyes: Injury is unlikely. Stain for evidence of corneal injury. Consult ophthalmologist.

Skin: May cause moderate irritation. Treat as any contact dermatitis. Known or suspected weak sensitizer. Not likely to be absorbed in acutely toxic amounts. Respiratory injury is unlikely.

SECTION 6: REACTIVITY DATA

Stability: Stable under normal conditions. Prolonged excessive heat may cause partial degradation.

Incompatibility: Active acids and bases

Hazardous Decomposition Products: None under normal conditions.

Hazardous Polymerization: Will not occur by itself, but masses of more than 3-5 pounds of product plus an aliphatic amine may cause irreversible reaction with considerable heat buildup.

SECTION 7: SPILL, LEAK AND DISPOSAL PROCEDURES

Action to Take For Spills: (Use appropriate safety equipment.) Scrape up. Residual resin can be removed by use of non-flammable solvent such as methylene chloride.

Disposal Method: Do not dump into any sewers, on the ground or into any body of water. All disposal methods must be compliance with all federal, state and local law and regulations.

SECTION 8: SPECIAL HANDLING INFORMATION

Ventilation: Sufficient to minimize vapor exposure if generated.

Respiratory Protection: None likely needed.

Protective Clothing: Clean, body-covering clothing. Disposable plastic or rubber gloves. Disposable containers and paper in work area

Eye Protection: Safety glasses.

SECTION 9: SPECIAL PRECAUTIONS IN HANDLING AND STORAGE AND ADDITIONAL INFORMATION

Precautions to Be Taken In Handling and Storage: None except normal handling care. Practice good caution and personal cleanliness to avoid eye and skin contact. Avoid breathing vapors if generated.

SECTION 10: TRANSPORTATION REQUIREMENTS

Proper Shipping Name: Not Regulated

Hazardous Class: Not Regulated

ID Number: Not Regulated

Packing Group: Not Regulated

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED IS MADE.



ABATRON, INC.

5501 - 95th Ave., Kenosha, WI 53144 U.S.A
(262) 653-2000 www.abatron.com
24 Hour Emergency No: 800/424-9300

Material Safety Data Sheet

CODE: WoodEpoxy B

Page: 2

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Code: WoodEpoxy B
Product Name: WoodEpoxy B
Class: Formulated Epoxy Coreactant

Date Prepared: 06/29/2006
Type: Curing-Agent Paste

SECTION 2: HAZARDOUS INGREDIENTS

Trade Secret: Proprietary Formulated Amines

SECTION 3: PHYSICAL DATA

Boiling Point: NA
Vapor Press: NA
Vapor Density (Air=1): NA
Appearance and Odor: Tan thixotropic paste. Light ammonia odor.

Sol. In Water: NA
Sp. Gravity: <1
% Volatile by Vol.: <0.1

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

Flash Point: >450° F
Method Used: ASTM D92-96
Extinguishing Media: Foam, CO₂, dry chemical.
Special Fire Fighting Equipment and Hazards: None

Flammable Limits (STP in Air):
LFL: Not deter. **UFL:** Not deter.

SECTION 5: HEALTH HAZARD DATA

Occupational Exposure Limits:
OSHA PEL/TWA: Not established
ACGIH TLV/TWA: Not established

PEL/STEL: Not established

Ingestion: LD50 >16 g/kg
Eye Contact: Extreme irritation.
Skin Contact: Only minor irritation. Primary irritation test score 1.2.
Skin Absorption: No significant hazard. LD50 = 6.5 g/kg
Inhalation: Not likely a problem at room temperature. Vapors from heated Material may be irritating.
Effect Of Overexposure: May cause skin sensitization. None other known.

First Aid Procedures:

Eyes: Irrigate with flowing water immediately for at least 10 minutes. Refer to medical personnel.
Skin: Wipe off excess. Scrub with soap and water followed by water rinse. Wash clothing before reuse.
Inhalation: Remove to fresh air if effects occur. Consult medical personnel.
Ingestion: Low in toxicity. Induce vomiting if large amounts are ingested.

Note to Physician:

Eyes: Extremely irritating. Stain for evidence of corneal injury. Consult ophthalmologist.
Skin: Acute dermal toxicity. Treat as contact dermatitis. Known or suspected sensitizer. Not likely to be absorbed in acutely toxic amounts.

Note to Physician:

Eyes: Extremely irritating. Stain for evidence of corneal injury. Consult ophthalmologist.
Skin: Acute dermal toxicity. Treat as contact dermatitis. Known or suspected sensitizer. Not likely to be absorbed in acutely toxic amounts.
Respiratory: Injury is unlikely.
Systemic: Human effects not established. No specific antidote. Treatment should be based on the sound judgment of the physician and the individual reaction of the patient.

SECTION 6: REACTIVITY DATA

Stability: Stable under normal conditions. Prolonged excessive heat may cause partial degradation.
Incompatibility: None known.
Hazardous Decomposition Products: None under normal conditions.
Hazardous Polymerization: None.

SECTION 7: SPILL, LEAK AND DISPOSAL PROCEDURES

Action To Take For Spills: (Use appropriate safety equipment.) Scrape up. Scrub with 5% acetic acid to emulsify. Rinse with very hot water.
Disposal Method: Do not dump into any sewers, on the ground or into any body of water. All disposal methods must be compliance with all federal, state and local law and regulations.

SECTION 8: SPECIAL HANDLING INFORMATION

Ventilation: Sufficient to minimize vapor exposure if generated.
Respiratory Protection: none likely needed.
Protective Clothing: Clean, body-covering clothing. Disposable plastic or rubber gloves. Disposable containers and paper in work area.
Eye Protection: Safety glasses.

SECTION 9: SPECIAL PRECAUTIONS IN HANDLING AND STORAGE AND ADDITIONAL INFORMATION

Precautions to Be Taken In Handling and Storage: None except normal handling care. Practice good caution and personal cleanliness to avoid eye and skin contact. Avoid breathing vapors if generated.

SECTION 10: TRANSPORTATION REQUIREMENTS

Proper Shipping Name:	Not Regulated
Hazardous Class:	Not Regulated
ID Number:	Not Regulated
Packing Group:	Not Regulated

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED IS MADE.