

# MATERIAL SAFETY DATA SHEET

**PRODUCT NAME:** ANCHORSEAL - Winterized with propylene glycol

**DATE PREPARED:** March 4, 2008

## 1. IDENTIFICATION

Identity (as used on label and listings): ANCHORSEAL – Winterized with propylene glycol

Chemical Family/Specific Type: Water-based emulsions / aqueous emulsion of paraffin wax

Manufacturer: U-C Coatings Corporation

Telephone Number: 716-833-9366

P. O. Box 1066

Fax Number: 716-833-0120

Buffalo, NY 14215 U.S.A.

Emergency Telephone No.: 716-833-9366

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>Approximate %</u>	<u>CAS No.</u>
Petroleum Wax	45 - 50%	64742 - 61 - 6
Propylene Glycol	5%	57 - 55 - 6

*No reportable quantities of any hazardous ingredients are present. No toxic chemical(s) subject to reporting requirements of Section 313 of Title III and of 40 CFR 372 are present.*

## 3. HAZARDS RATINGS (HMIS) OF THE PRODUCT

**HEALTH:** 1

**FLAMMABILITY:** 1

Explanation of Hazards Ratings:

**REACTIVITY:** 0

**PROTECTIVE EQUIPMENT:** C

0 = Minimal Hazard

1 = Slight Hazard

2 = Moderate Hazard

3 = Serious Hazard

4 = Severe Hazard

Protective Equipment:

C = safety glasses + gloves + apron

General: ANCHORSEAL is generally harmless to handle provided that certain precautions normally taken when handling paints and chemicals are observed.

Inhalation: Vapor pressure is very low, so inhalation is not normally a problem. Avoid heating the product - heating above 212°F/100°C may cause vapors causing irritation of the nose, throat and respiratory system.

Eye Contact: Causes irritation to the eyes.

Skin Contact: Repeated or prolonged skin contact may cause dermatitis or defatting.

Ingestion: Not expected to be acutely toxic. May cause irritation of digestive tract.

## 4. FIRST AID MEASURES

Inhalation: If irritation or headache occurs, remove to fresh air. Seek medical attention if symptoms continue.

Eye Contact: Flush eyes immediately with large amounts of water, using soap if possible. If irritation continues, seek medical attention.

Skin Contact: Wash skin with soap and water. Remove contaminated clothing. If irritation persists, seek medical attention.

Ingestion: Do not induce vomiting (aspiration hazard). Seek medical help immediately for ingestion of wax and water emulsion.

## 5. FIRE FIGHTING MEASURES

Flash Point: No flash – boils at 190° - 212°F / 88° - 100°C

Extinguishing Media: Water spray, dry chemical, carbon dioxide (CO<sub>2</sub>), foam. Do not direct solid stream of water or foam into burning pools.

Fire Fighting Instructions: Avoid breathing smoke and vapor.

Fire Fighting Equipment: Self-contained breathing apparatus and protective clothing.

Other Fire or Explosion Hazards: Incomplete combustion can produce carbon monoxide.

## 6. ACCIDENTAL RELEASE MEASURES

SPILLS OR LEAKS: Large spills: contain with dikes, collect, and filter for reuse. Small spills: collect or absorb with oil absorbent pads. Clean contaminated areas with soap and water. All spill response and disposal should be carried out in accordance with national and local requirements.

**PRODUCT NAME: ANCHORSEAL- Winterized with propylene glycol****7. HANDLING AND STORAGE**

Handling: Do not swallow; avoid exposure to eyes and skin; use in areas with normal ventilation.

Storage: Store at ambient temperature. Avoid high heat or open flames.

General: Keep containers closed to minimize evaporation and skin formation. Store above 32°F / 0°C for ease of use and to avoid gradual thickening at lower temperatures.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure Limits: None established for this product.

Ventilation: Good ventilation in work area, atmospheric pressure.

Personal Protection: Eyes: safety glasses or splash goggles

Hands: rubber gloves

Other: synthetic apron for cleanliness

**9. PHYSICAL & CHEMICAL CHARACTERISTICS**

Appearance and Odor: Creamy white or colored liquid of paint-like consistency; slightly oily/waxy odor.

Boiling Point: 212°F / 100°C

Specific Gravity: .98

Vapor Pressure: same as water

Melting Point: 25°F / -4°C

Vapor Density (air = 1): same as water

Evaporation Rate (butyl acetate = 1): < 1

Solubility In Water: infinitely diluteable

Flash Point: No flash – boils at 190° - 212°F / 88° - 100°C

Volatile Organic Compounds: none

(Flash point of dried wax is > 400°F/200°C)

Volatile Hazardous Air Pollutants: none

**10. STABILITY AND REACTIVITY**

Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: None known.

Materials to Avoid: Strong oxidizing agents.

Hazardous Polymerization: Will not occur.

Hazardous Decomposition: Burning may produce carbon monoxide and/or carbon dioxide.

**11. TOXICOLOGICAL INFORMATION**

Product is practically non-toxic and non-irritating.

**12. ECOLOGICAL INFORMATION**

No data available.

**13. DISPOSAL CONSIDERATIONS**

Not a hazardous waste. Where recovery and reuse is not possible, dry water out of product and dispose of as industrial wax waste or by incineration where permitted under national and local regulations.

**14. TRANSPORTATION INFORMATION**

ADR/RID: Not regulated

IMDG: Not regulated

ICAO/IATA: Not regulated

**15. REGULATORY INFORMATION**

The ingredients in this product are in the TSCA, MITI, AICS, DSL inventories.

**16. OTHER INFORMATION**

Please consult product and application information for the proper use of this product.